

## PCT

## INTERNATIONAL SEARCH REPORT

(PCT Article 18 and Rules 43 and 44)

Applicant's or agent's file reference <b>87078/VRD/DW</b>	<b>FOR FURTHER ACTION</b> see Notification of Transmittal of International Search Report (Form PCT/ISA/220) as well as, where applicable, item 5 below.	
International application No. <b>PCT/GB 98/ 00956</b>	International filing date (day/month/year) <b>31/03/1998</b>	(Earliest) Priority Date (day/month/year) <b>01/04/1997</b>
Applicant <b>SGS-THOMSON MICROELECTRONICS LIMITED et al.</b>		

This International Search Report has been prepared by this International Searching Authority and is transmitted to the applicant according to Article 18. A copy is being transmitted to the International Bureau.

This International Search Report consists of a total of 3 sheets.

☒ It is also accompanied by a copy of each prior art document cited in this report.

1. ☐ Certain claims were found unsearchable (see Box I).

2. ☐ Unity of invention is lacking (see Box II).

3. ☐ The international application contains disclosure of a nucleotide and/or amino acid sequence listing and the international search was carried out on the basis of the sequence listing

☐ filed with the international application.

☐ furnished by the applicant separately from the international application,

☐ but not accompanied by a statement to the effect that it did not include matter going beyond the disclosure in the international application as filed.

☐ Transcribed by this Authority

4. With regard to the title, ☒ the text is approved as submitted by the applicant

☐ the text has been established by this Authority to read as follows:

5. With regard to the abstract,

☒ the text is approved as submitted by the applicant

☐ the text has been established, according to Rule 38.2(b), by this Authority as it appears in Box III. The applicant may, within one month from the date of mailing of this International Search Report, submit comments to this Authority.

6. The figure of the drawings to be published with the abstract is:

Figure No. 1 ☒ as suggested by the applicant.

☐ because the applicant failed to suggest a figure.

☐ because this figure better characterizes the invention.

☐ None of the figures.

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 98/00956

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 6 H04B1/20

According to International Patent Classification(IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H04B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 94 15 811 U (METZ WERKE GMBH & CO KG) 17 November 1994	1-9, 11, 14, 17, 19, 21, 22
A	see the whole document	10, 12, 13, 18, 20
X	US 5 081 534 A (GEIGER ERICH ET AL) 14 January 1992	1, 2, 4, 5, 7, 11, 15-17, 19, 21, 22
A	see line 13 - column 3, line 25; figures 1, 2	3, 6, 8-10, 12-14, 18, 20

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

29 July 1998

Date of mailing of the international search report

06/08/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Andersen, J.G.

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 98/00956

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 109 222 A (WELTY JOHN) 28 April 1992	1,2,4,6, 8-11, 15-17, 19,21,22
A	see column 7, line 24 - column 8, line 19; figure 5	3,5,7, 12-14, 18,20
A	EP 0 535 749 A (D2B SYSTEMS CO LTD) 7 April 1993 see page 2, line 25 - line 31	1,12,13, 15-17,20

## INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 98/00956

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
DE 9415811	U	17-11-1994	DE 19534883 A	11-04-1996
US 5081534	A	14-01-1992	DE 3827050 A	15-02-1990
			AU 630367 B	29-10-1992
			AU 4037989 A	05-03-1990
			DE 58907163 D	14-04-1994
			DK 13591 A	25-01-1991
			WO 9001847 A	22-02-1990
			EP 0354459 A	14-02-1990
			EP 0433297 A	26-06-1991
			FI 100288 B	31-10-1997
			HK 7696 A	26-01-1996
			JP 4500142 T	09-01-1992
US 5109222	A	28-04-1992	NONE	
EP 0535749	A	07-04-1993	FI 924447 A	05-04-1993
			JP 5260058 A	08-10-1993
			US 5574965 A	12-11-1996

Our ref: 87078/VRD/AEM/pkh

6 October 1998

European Patent Attorneys  
Chartered Patent Attorneys  
Trade Mark Agents

Your ref:

BY FACSIMILE

W I P O  
34 Chemin des Colombettes  
1211 Geneva 20  
Switzerland

CC 7

Page White & Farrer  
54 Doughty Street  
London WC1N 2LS  
Telephone 0171 831 7929  
Facsimile 0171 831 8040  
Telex 8955681  
email@pagewhite.co.uk

Dear Sirs

**International Patent Application No. PCT/GB98/00956**  
**SGS-Thomson Microelectronics Limited**

Further to the issuance of the International search report on the above application, dated 6th August 1998, we hereby submit new claims 1 to 16 to replace claims 1 to 22 currently on file.

The claims have been amended to overcome the X-rated documents cited in the search report in particular US 5,081,534.

The independent claims are based on former independent claims 15, 16 and 21 but further restricted to encompass signals received from a broadcast medium. This is not found in US 5,081,534. The basis for the amendments may be found on page 10, paragraph 2, page 15, paragraph 4 and page 16, paragraph 3, and in former dependent claims 14 and 18.

Yours faithfully

DRIVER, Virginia Rozanne  
Authorised Representative

Enc.

Directors  
R Palmer  
D J Richards  
P D Jenkins  
Mrs V R Driver  
J N Daniels

Associate Directors  
Miss K C Style  
Ms N Shackleton  
P R Slingsby  
W J Neobard  
J P Cornish

CM Hill

Consultant  
A Pendlebury

CLAIMS:

1. A method of controlling first and second remote controlled apparatus, the first apparatus being operatively responsive to first control signals associated with a first remote control device and signals from a broadcast medium, and the second apparatus being operatively responsive to second control signals associated with a second remote control device, the method comprising:
  - storing said second control signals in said first apparatus;
  - receiving the first control signals from the first remote control device at said first apparatus;
  - accessing said stored second control signals responsive to selected ones of said first control signals;
  - transmitting accessed second control signals to said second apparatus, wherein the first apparatus remotely controls the second apparatus responsive to selected ones of the first control signals from the first remote control device;
  - receiving, at said first apparatus, signals from the broadcast medium which are transmitted to said second apparatus as second control signals to remotely control the second apparatus.
2. The method of claim 1, wherein said first apparatus remotely controls said one or more second apparatus.
3. A method according to claim 1 or claim 2, characterised in that said first apparatus is a set top box receiver.
4. A method according to any one of claims 1 to 3, characterised in that said one or more second apparatus include a video recorder and a television.
5. A method according to any of claims 1 to 4, characterised in that said one or more second apparatus include a sound system.

6. A method according to any of claims 1 to 5, characterised in that said one or more second apparatus include home automation apparatus.
7. A method according to any of claims 1 to 6, characterised in that said second control signals are received in response to a request from said first apparatus from said one or more second remote control devices.
8. A method according to any of claims 1 to 6 characterised in that said second control signals are received as part of a predetermined sequence from a portable storage medium.
9. A method according to claim 8 characterised in that said portable storage medium is a smartcard.
10. A method according to any of claims 1 to 8, characterised in that second control signals are received as part of a predetermined sequence from the broadcast medium.
11. A remotely controlled apparatus, operatively responsive to first control signals and signals from a broadcast medium, comprising:
  - first receiving means for receiving said first control signals from first remote control device and second receiving means for receiving said signals from the broadcast medium;
  - storage means for storing second control signals associated with a second remotely controlled apparatus operatively responsive to said second control signals;
  - control means for accessing said stored second control signals responsive to selected ones of said first control signals;
  - transmitting means for transmitting said accessed second control signals to said remotely controlled apparatus, whereby the remotely controlled apparatus remotely controls the second remotely controlled apparatus,

wherein the transmitting means is further operative to transmit said accessed signals from the broadcast medium to said remotely controlled apparatus as second control signals, to remotely control the second remotely controlled apparatus;

12. The remotely controlled apparatus of claim 11, wherein said control means stores said second control signals in said storage means.

13. The remotely controlled apparatus of claim 11 or 12, wherein said receiving means receives said second control signals from the second remote control device.

14. The remotely controlled apparatus of claim 13, wherein the storage means comprises a smart card.

15. A remote control system comprising:

- a first remotely controlled apparatus operationally responsive to first control signals associated with a first remote control device and signals associated with a broadcast medium;

- a second remotely controlled apparatus operatively responsive to second control signals associated with a second remote control device, wherein said first apparatus transmits said second control signals, to remotely control the second apparatus, responsive to selected ones of said first control signals as selected by said second control signals; and

- transmits said signals associated with the broadcast medium, to remotely control the second apparatus.

16. The remote control system of claim 15 in which the first remotely controlled apparatus comprises the remotely controlled apparatus of any one of claims 11 to 14.



# PCT

## REQUEST

The undersigned requests that the present international application be processed according to the Patent Cooperation Treaty.

For receiving Office use only

International Application No.

International Filing Date

Name of receiving Office and "PCT International Application"

Applicant's or agent's file reference  
(if desired) (12 characters maximum)

### Box No. I TITLE OF INVENTION

A METHOD FOR REMOTELY CONTROLLING A PLURALITY OF APPARATUS  
USING A SINGLE REMOTE CONTROL DEVICE

### Box No. II APPLICANT

Name and address: (Family name followed by given name; for a legal entity, full official designation. The address must include postal code and name of country. The country of the address indicated in this Box is the applicant's State (i.e. country) of residence if no State of residence is indicated below.)

SGS-THOMSON MICROELECTRONICS LIMITED  
1000 AZTEC WEST  
ALMONDSBURY  
BRISTOL BS32 4SQ  
UNITED KINGDOM

☐ This person is also inventor.

Telephone No.

Facsimile No.

Teleprinter No.

State (i.e. country) of nationality:  
GB

State (i.e. country) of residence:  
GB

This person is applicant  
for the purposes of:

☐ all designated  
States

☒ all designated States except  
the United States of America

☐ the United States  
of America only

☐ the States indicated in  
the Supplemental Box

### Box No. III FURTHER APPLICANT(S) AND/OR (FURTHER) INVENTOR(S)

Name and address: (Family name followed by given name; for a legal entity, full official designation. The address must include postal code and name of country. The country of the address indicated in this Box is the applicant's State (i.e. country) of residence if no State of residence is indicated below.)

HULME PETER JOHN  
10 ST. MICHAEL'S DRIVE  
WATFORD  
HERTFORDSHIRE WD2 7JN  
UNITED KINGDOM

This person is:

☐ applicant only

☒ applicant and inventor

☐ inventor only (If this check-box  
is marked, do not fill in below.)

State (i.e. country) of nationality:  
GB

State (i.e. country) of residence:  
GB

This person is applicant  
for the purposes of:

☐ all designated  
States

☐ all designated States except  
the United States of America

☒ the United States  
of America only

☐ the States indicated in  
the Supplemental Box

☐ Further applicants and/or (further) inventors are indicated on a continuation sheet.

### Box No. IV AGENT OR COMMON REPRESENTATIVE; OR ADDRESS FOR CORRESPONDENCE

The person identified below is hereby/has been appointed to act on behalf  
of the applicant(s) before the competent International Authorities as:

☒ agent

☐ common representative

Name and address: (Family name followed by given name; for a legal entity, full official designation. The address must include postal code and name of country.)

DRIVER VIRGINIA ROZANNE  
PAGE WHITE & FARRER  
54 DOUGHTY STREET  
LONDON WC1N 2LS  
UNITED KINGDOM

Telephone No.

0171 831-7929

Facsimile No.

0171 831-8040

Teleprinter No.

8955681

☐ Mark this check-box where no agent or common representative is/has been appointed and the space above is used instead to indicate a special address to which correspondence should be sent.

**Box No.V DESIGNATION OF STATES**

The following designations are hereby made under Rule 4.9(a) (mark the applicable check-boxes; at least one must be marked):

**Regional Patent**

- ☐ **AP** ARIPO Patent: GH Ghana, GM Gambia, KE Kenya, LS Lesotho, MW Malawi, SD Sudan, SZ Swaziland, UG Uganda, ZW Zimbabwe, and any other State which is a Contracting State of the Harare Protocol and of the PCT
- ☐ **EA** Eurasian Patent: AM Armenia, AZ Azerbaijan, BY Belarus, KG Kyrgyzstan, KZ Kazakhstan, MD Republic of Moldova, RU Russian Federation, TJ Tajikistan, TM Turkmenistan, and any other State which is a Contracting State of the Eurasian Patent Convention and of the PCT
- ☒ **EP** European Patent: AT Austria, BE Belgium, CH and LI Switzerland and Liechtenstein, DE Germany, DK Denmark, ES Spain, FI Finland, FR France, GB United Kingdom, GR Greece, IE Ireland, IT Italy, LU Luxembourg, MC Monaco, NL Netherlands, PT Portugal, SE Sweden, and any other State which is a Contracting State of the European Patent Convention and of the PCT
- ☐ **OA** OAPI Patent: BF Burkina Faso, BJ Benin, CF Central African Republic, CG Congo, CI Côte d'Ivoire, CM Cameroon, GA Gabon, GN Guinea, ML Mali, MR Mauritania, NE Niger, SN Senegal, TD Chad, TG Togo, and any other State which is a member State of OAPI and a Contracting State of the PCT (if other kind of protection or treatment desired, specify on dotted line)

**National Patent (if other kind of protection or treatment desired, specify on dotted line):**

- |   |  |
|---|--|
| <input type="checkbox"/> AL Albania                               | <input type="checkbox"/> LT Lithuania                                  |
| <input type="checkbox"/> AM Armenia                               | <input type="checkbox"/> LU Luxembourg                                 |
| <input type="checkbox"/> AT Austria                               | <input type="checkbox"/> LV Latvia                                     |
| <input type="checkbox"/> AU Australia                             | <input type="checkbox"/> MD Republic of Moldova                        |
| <input type="checkbox"/> AZ Azerbaijan                            | <input type="checkbox"/> MG Madagascar                                 |
| <input type="checkbox"/> BA Bosnia and Herzegovina                | <input type="checkbox"/> MK The former Yugoslav Republic of Macedonia  |
| <input type="checkbox"/> BB Barbados                              |  |
| <input type="checkbox"/> BG Bulgaria                              | <input type="checkbox"/> MN Mongolia                                   |
| <input type="checkbox"/> BR Brazil                                | <input type="checkbox"/> MW Malawi                                     |
| <input type="checkbox"/> BY Belarus                               | <input type="checkbox"/> MX Mexico                                     |
| <input type="checkbox"/> CA Canada                                | <input type="checkbox"/> NO Norway                                     |
| <input type="checkbox"/> CH and LI Switzerland and Liechtenstein  | <input type="checkbox"/> NZ New Zealand                                |
| <input type="checkbox"/> CN China                                 | <input type="checkbox"/> PL Poland                                     |
| <input type="checkbox"/> CU Cuba                                  | <input type="checkbox"/> PT Portugal                                   |
| <input type="checkbox"/> CZ Czech Republic                        | <input type="checkbox"/> RO Romania                                    |
| <input type="checkbox"/> DE Germany                               | <input type="checkbox"/> RU Russian Federation                         |
| <input type="checkbox"/> DK Denmark                               | <input type="checkbox"/> SD Sudan                                      |
| <input type="checkbox"/> EE Estonia                               | <input type="checkbox"/> SE Sweden                                     |
| <input type="checkbox"/> ES Spain                                 | <input type="checkbox"/> SG Singapore                                  |
| <input type="checkbox"/> FI Finland                               | <input type="checkbox"/> SI Slovenia                                   |
| <input type="checkbox"/> GB United Kingdom                        | <input type="checkbox"/> SK Slovakia                                   |
| <input type="checkbox"/> GE Georgia                               | <input type="checkbox"/> SL Sierra Leone                               |
| <input type="checkbox"/> GH Ghana                                 | <input type="checkbox"/> TJ Tajikistan                                 |
| <input type="checkbox"/> GM Gambia                                | <input type="checkbox"/> TM Turkmenistan                               |
| <input type="checkbox"/> GW Guinea-Bissau                         | <input type="checkbox"/> TR Turkey                                     |
| <input type="checkbox"/> HU Hungary                               | <input type="checkbox"/> TT Trinidad and Tobago                        |
| <input type="checkbox"/> ID Indonesia                             | <input type="checkbox"/> UA Ukraine                                    |
| <input type="checkbox"/> IL Israel                                | <input type="checkbox"/> UG Uganda                                     |
| <input type="checkbox"/> IS Iceland                               | <input checked="" type="checkbox"/> <b>US</b> United States of America |
| <input checked="" type="checkbox"/> <b>JP</b> Japan               |  |
| <input type="checkbox"/> KE Kenya                                 | <input type="checkbox"/> UZ Uzbekistan                                 |
| <input type="checkbox"/> KG Kyrgyzstan                            | <input type="checkbox"/> VN Viet Nam                                   |
| <input type="checkbox"/> KP Democratic People's Republic of Korea | <input type="checkbox"/> YU Yugoslavia                                 |
|   | <input type="checkbox"/> ZW Zimbabwe                                   |
| <input type="checkbox"/> KR Republic of Korea                     |  |
| <input type="checkbox"/> KZ Kazakhstan                            |  |
| <input type="checkbox"/> LC Saint Lucia                           |  |
| <input type="checkbox"/> LK Sri Lanka                             |  |
| <input type="checkbox"/> LR Liberia                               |  |
| <input type="checkbox"/> LS Lesotho                               |  |

Check-boxes reserved for designating States (for the purposes of a national patent) which have become party to the PCT after issuance of this sheet:

In addition to the designations made above, the applicant also makes under Rule 4.9(b) all designations which would be permitted under the PCT except the designation(s) of \_\_\_\_\_

The applicant declares that those additional designations are subject to confirmation and that any designation which is not confirmed before the expiration of 15 months from the priority date is to be regarded as withdrawn by the applicant at the expiration of that time limit. (Confirmation of a designation consists of the filing of a notice specifying that designation and the payment of the designation and confirmation fees. Confirmation must reach the receiving Office within the 15-month time limit.)

**Supplemental Box** *If the Supplemental Box is not used, this sheet need not be included in the request.*

*Use this box in the following cases:*

**1. If, in any of the Boxes, the space is insufficient to furnish all the information:**

*in particular:*

(i) *if more than two persons are involved as applicants and/or inventors and no "continuation sheet" is available:*

*in such case, write "Continuation of Box No. ..." [indicate the number of the Box] and furnish the information in the same manner as required according to the captions of the Box in which the space was insufficient;*

(ii) *if, in Box No. II or in any of the sub-boxes of Box No. III, the indication "the States indicated in the Supplemental Box" is checked:*

*in such case, write "Continuation of Box No. III" and indicate for each additional person the same type of information as required in Box No. III. The country of the address indicated in this Box is the applicant's State (i.e. country) of residence if no State of residence is indicated below;*

(iii) *if, in Box No. II or in any of the sub-boxes of Box No. III, the inventor or the inventor/applicant is not inventor for the purposes of all designated States or for the purposes of the United States of America:*

*in such case, write "Continuation of Box No. II" or "Continuation of Box No. III" or "Continuation of Boxes No. II and No. III" (as the case may be), indicate the name of the applicant(s) involved and, next to (each) such name, the State(s) (and/or, where applicable, ARIPO, Eurasian, European or OAPI patent) for the purposes of which the named person is applicant;*

(iv) *if, in addition to the agent(s) indicated in Box No. IV, there are further agents:*

*in such case, write "Continuation of Box No. II" or "Continuation of Box No. III" or "Continuation of Boxes No. II and No. III" (as the case may be), indicate the name of the inventor(s) and, next to (each) such name, the State(s) (and/or, where applicable, ARIPO, Eurasian, European or OAPI patent) for the purposes of which the named person is inventor;*

(v) *if, in Box No. V, the name of any State (or OAPI) is accompanied by the indication "patent of addition," or "certificate of addition," or if, in Box No. V, the name of the United States of America is accompanied by an indication "Continuation" or "Continuation-in-part":*

*in such case, write "Continuation of Box No. IV" and indicate for each further agent the same type of information as required in Box No. IV;*

(vi) *if there are more than three earlier applications whose priority is claimed:*

*in such case, write "Continuation of Box No. V" and the name of each State involved (or OAPI), and after the name of each such State (or OAPI), the number of the parent title or parent application and the date of grant of the parent title or filing of the parent application;*

**2. If the applicant claims, in respect of any designated Office, the benefits of provisions of the national law concerning non-prejudicial disclosures or exceptions to lack of novelty:**

*in such case, write "Statement Concerning Non-Prejudicial Disclosures or Exceptions to Lack of Novelty" and furnish that statement below.*

# CONTINUATION OF BOX IV

PENDLEBURY, DR. ANTHONY (GB)  
PALMER, ROGER (GB)  
JENKINS, PETER DAVID (GB)  
DANIELS, JEFFREY NICHOLAS (GB)  
RICHARDS, DAVID JOHN (GB)  
STYLE, KELDA CAMILLA KAREN (GB)  
NEOBARD, WILLIAM JOHN (GB)  
SHACKLETON, NICOLA (GB)  
SLINGSBY, PHILIP ROY (GB)  
WILLIAMS, DAVID JOHN (GB)  
HIGGIN, PAUL (GB)  
HILL, CHRISTOPHER MICHAEL (GB)

of PAGE WHITE & FARRER, 54 DOUGHTY STREET, LONDON WC1N 2LS, GB

Tel: 0171 831-7929

Fax: 0171 831-8040

Telex: 8955681

**Box No. VI PRIORITY CLAIM**Further priority claims are indicated in the Supplemental Box ☐

The priority of the following earlier application(s) is hereby claimed:

Country (in which, or for which, the application was filed)	Filing Date (day/month/year)	Application No.	Office of filing (only for regional or international application)
item (1) GB	01.04.1997	9706620.3	
item (2)			
item (3)			

Mark the following check-box if the certified copy of the earlier application is to be issued by the Office which for the purposes of the present international application is the receiving Office (a fee may be required):

☒ The receiving Office is hereby requested to prepare and transmit to the International Bureau a certified copy of the earlier application(s) identified above as item(s): (1)**Box No. VII INTERNATIONAL SEARCHING AUTHORITY**

Choice of International Searching Authority (ISA) (If two or more International Searching Authorities are competent to carry out the international search, indicate the Authority chosen; the two-letter code may be used): ISA / EP

Earlier search Fill in where a search (international, international-type or other) by the International Searching Authority has already been carried out or requested and the Authority is now requested to base the international search, to the extent possible, on the results of that earlier search. Identify such search or request either by reference to the relevant application (or the translation thereof) or by reference to the search request:

Country (or regional Office): GB Date (day/month/year): 01.04.1997 Number: 9706620.3

**Box No. VIII CHECK LIST**

This international application contains the following number of sheets:

1. request : 4 sheets  
 2. description : 17 sheets  
 3. claims : 5 sheets  
 4. abstract : 1 sheets  
 5. drawings : 2 sheets

Total : 29 sheets

This international application is accompanied by the item(s) marked below:

1. ☐ separate signed power of attorney  
 2. ☐ copy of general power of attorney  
 3. ☐ statement explaining lack of signature  
 4. ☐ priority document(s) identified in Box No. VI as item(s):  
 5. ☒ fee calculation sheet  
 6. ☐ separate indications concerning deposited microorganisms  
 7. ☐ nucleotide and/or amino acid sequence listing (diskette)  
 8. ☒ other (specify): Form 23/77 Earlier Search Report

Figure No. \_\_\_\_\_ of the drawings (if any) should accompany the abstract when it is published.

**Box No. IX SIGNATURE OF APPLICANT OR AGENT**

Next to each signature, indicate the name of the person signing and the capacity in which the person signs (if such capacity is not obvious from reading the request).

DRIVER, VIRGINIA ROZANNE  
 (Authorised Representative)

For receiving Office use only

1. Date of actual receipt of the purported international application:	2. Drawings:
3. Corrected date of actual receipt due to later but timely received papers or drawings completing the purported international application:	<input type="checkbox"/> received:
4. Date of timely receipt of the required corrections under PCT Article 11(2):	<input type="checkbox"/> not received:
5. International Searching Authority specified by the applicant: ISA /	6. <input type="checkbox"/> Transmittal of search copy delayed until search fee is paid

For International Bureau use only

Date of receipt of the record copy by the International Bureau:




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>H04B 1/20</b>		<b>A1</b>	(11) International Publication Number: <b>WO 98/44647</b>
			(43) International Publication Date: 8 October 1998 (08.10.98)
(21) International Application Number: <b>PCT/GB98/00956</b>		(81) Designated States: JP, US, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(22) International Filing Date: 31 March 1998 (31.03.98)		<b>Published</b> <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	
(30) Priority Data: 9706620.3 1 April 1997 (01.04.97) GB			
(71) Applicant (for all designated States except US): SGS-THOMSON MICROELECTRONICS LIMITED [GB/GB]; 1000 Aztec West, Almondsbury, Bristol BS32 4SQ (GB).			
(72) Inventor; and (75) Inventor/Applicant (for US only): HULME, Peter, John [GB/GB]; 10 St. Michael's Drive, Watford, Hertfordshire WD2 7JN (GB).			
(74) Agents: DRIVER, Virginia, Rozanne et al.; Page White & Farrer, 54 Doughty Street, London WC1N 2LS (GB).			

(54) Title: A METHOD FOR REMOTELY CONTROLLING A PLURALITY OF APPARATUS USING A SINGLE REMOTE CONTROL DEVICE

## (57) Abstract

The present invention relates to a method of controlling one or more second apparatus from a first apparatus, which is responsive to first control signals from a first remote control device. The characteristic steps of the method comprise: providing the first remote control with additional operational functions, and corresponding third control signals, that correspond to functions of said second apparatus; receiving and storing in said first apparatus, as part of an initialisation procedure, second control signals that have corresponding third control signals, said second control signals being stored as second reference control signals in a storage medium; receiving said third control signals from said first remote control; receiving said second reference control signals from said storage medium; comparing said third control signals and said second reference control signals; and controlling, by means of said second reference control signals, said second apparatus, via said first apparatus, when said third control signals and said second reference control signals equal each other.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

- 1 -

Title of The Invention

A METHOD FOR REMOTELY CONTROLLING A PLURALITY OF APPARATUS  
USING A SINGLE REMOTE CONTROL DEVICE

BACKGROUND OF THE INVENTION1. Field of the Invention

The present invention relates to a method for remotely controlling apparatus.

More particularly, the present invention relates to a method for remotely controlling a plurality of apparatus using a single remote control device.

2. Background Art

In relatively recent times, apparatus such as televisions sets (TV), video recorders (VCR), music centres (HiFi), "set top box" receivers (STB), etc. have been supplied with their own individual remote control devices. The manufacturers of such apparatus use different, and usually unique, sets of control signals or codes for controlling, via remote control devices, each of these apparatus. Therefore, someone who has, for example, a TV, VCR, HiFi and a STB would expect to have four remote control devices: i.e. one remote control device for each apparatus; especially if the apparatus originated from different manufacturers.

Apart from the practical problems of managing, and often juggling, a plurality of remote control devices, an economic problem arises in that each remote control device comes with its own component and assembly cost. This cost is hidden within the cost of the apparatus, and is carried by the consumer. Additionally, each remote control has to be powered: again at a cost to the consumer. Typically this involves mean having between four and eight batteries for four remote control devices. The ultimate disposal of this number of batteries,

- 2 -

multiplied by a nation of consumers having a plurality of remote control devices, impacts upon the environment as time progresses.

There are some suppliers that offer, for example, a TV and VCR as a set, which has a single, combined, remote control device that can be used to operate both the TV and the VCR. However, relatively speaking it is not often that such TV/VCR sets are bought, as they tend to be aimed at the high end of the consumer/business market. Therefore, the majority of TV/VCR combinations tend to be incompatible in terms of being controlled via a single remote control device. Therefore, the impact of such TV/VCR sets does very little to alleviate the practical, economic and environmental problems mentioned above. Attempts have been made in recent times to provide consumers with what are generally known as 'universal' remote control devices. The purpose of such a universal remote control device is to alleviate the aforementioned problems. However, there are also problems associated with these universal remote control devices. These problems can be summarised as follows.

For the universal remote control device to be truly universal, it must contain the control codes or signals that correspond to all apparatus available on the market. Apart from the practical and economic problems of a manufacturer of such universal remote control devices having to keep abreast of all emerging new codes, the universal remote control device would require a significant amount of memory to store all the various codes. Such memory is relatively expensive especially if this memory comes as a "stand-a-lone" memory. Furthermore, once a universal remote control device is sold it would have to be updated if it is to be at all effective for the future. Such an updateable universal remote control device would require relatively more expensive, programmable memory in addition to circuitry for receiving and processing new data relating to the new codes, and controlling a memory write operation.



- 3 -

It should be noted that the majority of present day remote control devices are optically based and operate in the infra-red band of the light spectrum. However, for the purposes of this document all previous and future reference to a remote control device is intended to include all types of current, and indeed future, remote control device such as acoustic and radio frequency (RF) remote control devices.

#### OBJECTS & SUMMARY OF THE INVENTION

Accordingly, an aim of the present invention is to overcome the aforementioned problems and attributable drawbacks associated with the current state of the art.

The present invention provides a method of controlling a first apparatus, which is operatively responsive to first control signals from a first remote control device, said method comprising the following steps: receiving said first control signals; receiving first reference control signals CR1 from a storage medium, said first reference control signals corresponding to said first control signals; comparing said first control signals and said first reference control signals; and operatively controlling, said first apparatus in response to said first control signals when said first control signals and said first reference control signals equal each other, characterised in that, said method further comprises the following steps, which allow said first remote control device and said first apparatus to operatively control one or more second apparatus that are otherwise operatively responsive to respective second control signals from respective one or more second remote control devices: providing said first remote control device with additional operational functions, and corresponding third control signals, that respectively correspond to operational functions of said one or more second apparatus, said additional operational functions and third control signals being either selectively and/or permanently available; receiving and storing in said first apparatus, as part of an initialisation procedure and either in response to

- 4 -

a request and/or as part of a predetermined sequence, said second control signals that have corresponding third control signals, said received second control signals being stored as second reference control signals in said storage medium; receiving said third control signals from said first remote control device; receiving second reference control signals from said storage medium; comparing said third control signals and said second reference control signals; and operatively controlling, by means of said second reference control signals, said one or more second apparatus, via said first apparatus, when said third control signals and said second reference control signals equal each other.

Said first apparatus may be a satellite and/or cable set top box, STB, receiver or a video recorder, VCR, or television, TV, and said one or more second apparatus may respectively include a video recorder and a television or a set top box receiver and a television or a set top box receiver and a video recorder.

Said storage medium may be a memory such as a ROM, EPROM, EEPROM, or flash memory. Said one or more second apparatus may include a sound system HiFi, for example a combined radio, cassette player and CD player.

Said one or more second apparatus may include home automation apparatus such as automatic blinds/shutters, light switching, security cameras etc.

Said second control signals may be received in response to a request from said first apparatus from said one or more second remote control devices.

Said second control signals may be received as part of a predetermined sequence from a portable storage medium. Said portable storage medium may be a smartcard or some other 'chip-carrying' medium.

- 5 -

Said second control signals may be received as part of a predetermined sequence via said first apparatus's broadcast medium: the broadcast medium being, for example, a satellite dish receiver or a fibre optical cable and their respective associated hardware and system technologies.

The present invention provides a method for allowing a single apparatus, and its associated remote control device, to operatively control one or more other apparatus that are otherwise susceptible to being controlled by remote control signals.

The present invention thus provides a method for allowing a single apparatus, and its associated remote control device, to operatively control one or more other apparatus that are otherwise susceptible to being controlled by signals from their respective remote control devices.

The present invention provides a method for allowing a single apparatus, and its associated remote control device, to mimic or emulate the control signals of one or more other remote control devices so as to be able to operatively control the apparatus that would otherwise be controlled by the aforementioned other remote control devices.

According to the present invention there is provided a method for allowing practical, economical and environmental saving to be made by providing a method for allowing a single apparatus, and its associated remote control device, to operatively control one or more other apparatus that are otherwise susceptible to being controlled by signals from their respective remote control devices, i.e. providing a method for allowing a single apparatus, and its associated remote control device, to mimic or emulate the control signals of one or more other remote control devices so as to be able to operatively control the apparatus that would otherwise be controlled by the aforementioned other remote control devices.

- 6 -

The present invention provides a method for allowing a first apparatus to receive by interrogation, then store, remote control signals from one or more remote control devices, which are respectively associated with one or more second apparatus, in order that a single remote control device and its associated first apparatus can operatively control one or more second apparatus.

The present invention provides a method for allowing a first apparatus to receive then store remote control signals corresponding to those of one or more remote control devices, which are respectively associated with one or more second apparatus, in order that a single remote control device and its associated first apparatus can operatively control one or more second apparatus.

The invention also provides a method of controlling first and second remote controlled apparatus, the first apparatus being operatively responsive to first control signals associated with a first remote control device and the second apparatus being operatively responsive to second control signals associated with a second remote control device, the method comprising:

- storing said second control signals in said first apparatus;
- receiving the first control signals from the first remote control device at said first apparatus;
- accessing said stored second control signals responsive to selected ones of said first control signals; and
- transmitting said accessed second control signals to said second apparatus, wherein the first apparatus remotely controls the second apparatus responsive to selected ones of the first control signals from the first remote control device.

The invention further provides a remotely controlled apparatus, operatively responsive to first control signals, comprising:

- receiving means for receiving said first control signals from a first remote control device;

- 7 -

- storage means for storing second control signals associated with a second remotely controlled apparatus operatively responsive to said second control signals;

- control means for accessing said stored second control signals responsive to selected ones of said first control signals; and

- transmitting means for transmitting said accessed second control signals to said second remotely controlled apparatus, whereby the remotely controlled apparatus remotely controls the second remotely controlled apparatus.

Said control means may store said second control signals in said storage means.

The remotely controlled apparatus may further comprise broadcast receiving means for receiving broadcast signals, wherein said second control signals are received by said broadcast receiving means.

Said receiving means may receive said second control signals from the second remote control device.

The storage means may comprise a smart card.

The invention still further provides a remote control system comprising:

- a first remotely controlled apparatus operationally responsive to first control signals associated with a first remote control device;

- a second remotely controlled apparatus operatively responsive to second control signals associated with a second remote control device; wherein said first apparatus transmits said second control signals, to remotely control the second apparatus, responsive to selected ones of said first control signals.

The invention thus provides a remote control system in which

- 8 -

there are a plurality of remotely controlled devices associated with a respective plurality of remote control devices, each remote control device generating respective control signals, wherein one remotely controlled device remotely controls the other of the plurality of devices responsive to the control signals from the remote control device associated with the one remotely controlled device.

#### BRIEF DESCRIPTION OF THE DRAWINGS

These and other objects, as well as other advantages and features, of the present invention will become apparent in light of the following detailed description and accompanying drawings in which:

Figure 1 illustrates an embodiment of a typical system concept according to the present invention; and

Figure 2 illustrates an embodiment of a typical block diagram of circuitry within an apparatus according to the present invention.

#### DETAILED DESCRIPTION OF THE INVENTION

The following figures which illustrate the various embodiments of the present invention may incorporate the same or similar elements. Therefore, where the same or similar elements occur throughout the various figures, they will be designated in the same manner.

Figure 1 illustrates an embodiment of a typical system concept according to the present invention.

This system embodiment is illustrated as comprising a number of different apparatus, which include: a set-top-box receiver (STB) 10 for example a satellite set-top-box receiver, a video recorder (VCR) 20, a television set (TV) 30, and a sound system

- 9 -

(HiFi) 40.

The STB 10 receives, in the illustrated embodiment, signals via a satellite dish 45. Alternatively, the signals could be provided, via a cable, e.g. an optical cable, by a 'cable provider'. In the illustrated embodiment, the signals received by the satellite dish 45 are broadcast signals.

The STB 10 has a common operative connection(s), which could be a coaxial or scart cable for example, into the VCR 20 and the TV 30. The video is illustrated as having an operative cable connection(s) into the TV 30. The HiFi is illustrated as having no physical connection to either the STB 10, VCR 20 or TV 30. The arrangement of this illustrative embodiment of a system and its associated connections is known to those skilled in the art.

It should be noted that this embodiment could also include other apparatus, connected either physically or non-physically to the STB 10, such as home automation apparatus, for example automatic blinds, video security etc.

In this embodiment the STB 10 incorporates two blocks: a receiver block RX and a transmitter block TX. The overall system embodiment illustrates four remote control devices RC1-RC4. The latter three remote control devices RC2-RC3 are represented by dashed-line rectangles. The remote control devices RC2-RC4 are respectively associated with the VCR 20, TV 30, and HiFi 40. The remote control devices RC2, RC3, RC4 generate respective control signals CS2, CS3, CS4 to control the respective apparatus VCR 20, TV 30, HiFi 40. Each of the VCR 20, TV 30 and HiFi 40 include a receiver block RX for receiving the respective control signals. The receiver block RX of the STB 10 receives, as it would in the state of the art, control signals CS1 from the remote control device RC1.

According to one embodiment of the present invention, the STB

- 10 -

10 is capable of receiving (i.e. downloading), via the receiver block RX, and processing, respective control signals CS2-CS4 from the remote control devices RC2-RC4 that are respectively associated with the apparatus 20, 30 and 40.

According to another embodiment of the present invention, the STB 10 receives (i.e. download) the respective control signals CS2-CS4 associated with the remote control devices RC2-RC4 via a smart card, or another suitable medium, that is input to the STB 10 and/or via the satellite dish 45 or optical cable. Being able to download from a smartcard or from the broadcast signals, for example, has the advantage of not having to have the remote control devices RC2-RC4.

Also according to the present invention, the transmitter block TX of the STB 10 transmits control signals CS5 that are used to control the other apparatus 20, 30 and 40. Alternatively, the STB could control the other physically connected apparatus 20 and 30 via the cable.

It should be noted that in this particular arrangement, the STB 10 is illustrated as controlling the other apparatus 20, 30 and 40. However, the arrangement could be adapted such that any one of the other apparatus, such as the VCR 20 or the TV 30 for example, is used to control the other apparatus.

Figure 2 illustrates an embodiment of a typical block diagram of circuitry incorporated within the STB 10 apparatus according to the present invention. As mentioned hereinabove, this circuitry may alternatively be incorporated in other parts of the apparatus in the system.

This block diagram is illustrated as comprising: the receiver block RX; a microcontroller  $\mu C$ , a memory MEM; and the transmitter block TX.

According to one embodiment of the present invention the STB



- 11 -

10 is capable of receiving (i.e. downloading) via the receiver block RX, and processing, the respective control signals CS2-CS4 from the remote control devices RC2-RC4.

In this particular embodiment, the user initiates a software program within the STB 10 that allows the remote control devices RC2-RC4 to be interrogated. As a result of the interrogation, the remote control signals CS2-CS4 or codes associated with the other apparatus 20,30,40 are stored in a memory device preferably the memory MEM within the STB 10. The memory device may be, for example ROM, EPROM, EEPROM, flash memory etc. The remote control codes CS2-CS4 received from the remote control devices RC2-RC4 are operatively stored such that they correspond to known, or defined, respectively different remote control codes that are associated with the remote control device RC1. An important point to note is that the remote control signals CS1 of RC1 that correspond to the respective remote control signals CS2-CS4 from RC2-RC4 have to have the same associated functions: therefore when the "record" button on remote control device RC1 is pressed, the VCR 20 responds and records, and does not perform a different operation such as eject a tape.

The software program for carrying out the interrogation could be initiated either from the remote control device RC1 or by pressing a button(s) on the STB 10.

In this embodiment, the microcontroller  $\mu$ C of the STB 10 outwardly interfaces with the user, via the coax/scart connection(s), using the TV 30 for example.

The first issue to be addressed by the software program is to identify the type of apparatus the remote control codes CS2-CS4 associated with the remote control devices RC2-RC4 control. The software program for carrying out the interrogation may give the user a choice of options, via the TV 30 for example, from a predetermined list. Alternatively, the user could

- 12 -

interface with the STB 10 so as to enter a non-specified apparatus, and even non-specified functions, using the keypad of the remote control device RC1, such interface techniques are known to those skilled in the art.

It should be noted that the remote control device RC1 requires a keypad arrangement and control sequence that allowed it to work in various modes. For example, in a first, STB, mode M1, only those buttons, or button sequences, relating to the STB 10 functions would output corresponding remote control signals or codes for operating the STB 10. In a second, VCR, mode M2, only those buttons, or button sequences, relating to the VCR 20 functions would output corresponding remote control signals for operating the VCR 20, and so on. These various modes M1, M2, ... Mn etc, could be selected by pressing an appropriate button, or sequence of buttons, on RC1. In this example of distinct modes M1, M2, ... Mn etc, either the remote control device may add some distinguishing element to each transmitted remote control signal(s) or alternatively, RC1 may send a signal(s) to the STB 10 that sets up the STB 10 for the corresponding required mode.

Alternatively, there could be mixed-mode functioning. Mixed-mode functioning would be possible when in one mode, a function that was unique to another mode, i.e. another apparatus, was selected. For example, when in mode M1, a button on RC1 is pressed that corresponded to the VCR 'record' function. Since this 'record' function is unique to the VCR 20 then the need to enter into mode M2 is no longer necessary. In mixed-mode functioning, the need to enter into a particular mode would only be necessary when there is a button(s), or sequence of buttons, that are common to two or more apparatus, examples being numbers 0, 1, 2 ... n, volume +/-, channel +/- etc. It should also be noted that the remote control signals relating to the STB 10 apparatus will already be stored as reference remote control signals in the memory MEM associated with the microcontroller  $\mu$ C.

- 13 -

If, in this particular embodiment, the user selected an apparatus, for example a VCR 20, from a predetermined list of apparatus held within the memory MEM of the STB 10, then the STB 10 enters a software routine under the control of the "interrogation" software program. This routine requests, from another predetermined list, the user to press a sequence of buttons on remote control device RC2 etc. that corresponds to each of the various requests, i.e. the various functions associated with the VCR 20 etc. and each of the various requests would have a corresponding reference remote control signal that is associated with RC1. There could also be the option of the user defining functions that the STB 10 does not recognise and the user and/or microcontroller  $\mu C$  assigning a corresponding RC1 reference remote control signal.

In an example of setting up a VCR 20, the remote control signals CS2 transmitted by the VCR 20 remote control device RC2 are received by the receiver block RX of the STB, passed onto the microcontroller  $\mu C$  and then operatively stored in a memory location of the memory MEM as VCR reference remote control signals or codes along with associated remote control device RC1 reference remote control signals. For example, assume that the remote control signal from RC2 relating to the VCR's 'record' function was the four bit binary number 0110 and the corresponding remote control signal from RC1 relating to a VCR's 'record' function was the four bit binary number 1001: it should be noted that the codes from RC1 would have to be different from any of the codes associated with the other apparatus in order to avoid 'operational interference'. The binary number 1001 would already be stored in the memory MEM of the STB assuming it is predefined. Then, under control of the "interrogation" software program, it would be associated with the memory location of the binary number 0110 of the corresponding function, which would be stored in a different memory location. Therefore, the binary number 1001 would have a 'memory map' reference to the binary number 0110.

- 14 -

Having set up the memory MEM with the various reference remote control signals associated with the other apparatus and cross referencing them to corresponding remote control device RC1 reference control signals, during normal operation every time a remote control signal is received from remote control device RC1 by the microcontroller  $\mu C$ , via the receiver block RX of the STB the microcontroller  $\mu C$  compares this received remote control signal CS1 with the remote control device RC1 reference remote control signals stored in the memory MEM.

The remote control device RC1 may pause after each control signal CS1 associated with either the VCR, TV or HiFi to enable the transmitter block TX in the STB to send the appropriate control signals CS2, CS3 or CS4.

When the microcontroller  $\mu C$  identifies a remote control signal from remote control device RC1 that corresponds to a RC1 reference remote control signal it must firstly determine if the received signals or codes are associated with the STB 10 or with other apparatus. If the remote control signals received from remote control device RC1 are associated with the STB 10 then the microcontroller of the STB 10 is operated in accordance with the received signals or codes. If the RC1 received remote control signals are not associated with the STB 10 then the microcontroller of the STB 10 has to retrieve, from memory MEM, the stored remote control signals or codes to which the RC1 received signals or codes correspond. The microcontroller  $\mu C$  then outputs, via the transmitter block TX of the STB, the non-RC1 reference remote control signals or codes that correspond to the received and stored RC1 remote control signals or codes, which operatively controls the corresponding apparatus.

The receiver blocks RX may typically be a light sensitive semiconductor device that is capable of receiving signals, CS1-CS4 and CS5, in the infra-red part of the light spectrum since most remotely controlled apparatus use infra-red receivers and

- 15 -

transmitters. Alternatively, a receiver that was capable of receiving electrical or electro-magnetic signals or codes could be employed. Another example of a receiver block RX is a modem that is capable of receiving signals superimposed on the mains electricity supply of a household.

Likewise, the transmitter block TX of the STB would typically be a light emitting semiconductor device that is capable of transmitting signals, CS5, in the infra-red part of the light spectrum. Alternatively, a transmitter that is capable of transmitting electrical or electro-magnetic signals or codes could be employed. Another example of a transmitter block TX is a modem that is capable of transmitting signals superimposed upon the mains electricity supply of a household.

It should be noted that there could also be a plurality of different types of receivers and transmitters within an apparatus.

In a preferred embodiment of the current invention, the remote control signals corresponding to a particular apparatus could be input, or downloaded, via a smart card or via the broadcast medium, neither of which are illustrated.

The advantages of such an embodiment means that there is no longer a requirement for more than one remote control device. Therefore, all the disadvantages, such as cost and battery disposal, that is associated with a plurality of remote control devices would be alleviated. However, the former embodiment would serve well in the transitional period to this preferred embodiment.

In the case of the smartcard, the manufacturers of an apparatus would supply, with the apparatus, a smartcard that contained all of the remote control codes that are associated with the particular apparatus, or even a manufacturers range of apparatus. The advantages of smartcards are known and include

- 16 -

portability, programming flexibility, recyclability and low cost.

The 'master' apparatus in the example given above was the STB 10, but alternatively could be any of the other apparatus 20, 30 or 40. The 'master' apparatus may incorporate a smartcard reader and software that is operatively capable of extracting from the smartcard the remote control signals or codes associated with the 'slave' apparatus, for example a VCR 20, and storing and cross referencing such.

In the case of the broadcast medium, the remote control signals associated with various apparatus could be transmitted in the same or a similar manner as teletext, or even on a dedicated channel. The user could then, for example, select from a predefined list the type of 'slave' apparatus that is required to be controlled and then the 'master' device could automatically and operatively download, store and cross reference the remote control signals or codes associated with the particular 'slave' apparatus.

It should be noted that the arrangement, control and design of the various apparatus and the remote control device, and their interaction, embraces many fields, principles and techniques that are far too numerous and diverse to cover in any great detail in this document. Generally, for example, a system or protocol has to be set up such that the remote control signals are all read or downloaded, stored and cross referenced in a predetermined manner such that they have a corresponding, known, reference as to what their associated function and apparatus is; a protocol for selecting the 'master' and 'slave' devices would need to be established, since the inventor envisages that there will be at least some key apparatus, such as STB 10, VCR 20 and TV 30 that will all have the possibility of being 'master' apparatus. The design, layout and control of the remote control device has to take in a number of factors such as ease of use, the ability to control a plurality of

- 17 -

apparatus, and the possibility of defining whether 'custom' apparatus and functions can be added etc.

Such fields, principles and techniques and requirements to exploit the present invention will be apparent to those skilled in the art in light of this disclosure embodying the present invention.

Although this invention has been described in connection with certain preferred embodiments, and generalised, it should be understood that the present disclosure is to be considered as an exemplification of the principles of the invention and that there is no intention of limiting the invention to the disclosed embodiments. On the contrary, it is intended that all alternatives, modifications and equivalent arrangements as may be included within the scope of the appended claims be covered as part of this invention.

**Claims**

1. A method of controlling a first apparatus, which is operatively responsive to first control signals from a first remote control device, said method comprising the following steps:

- receiving said first control signals;
- receiving first reference control signals from a storage medium, said first reference control signals corresponding to said first control signals;
- comparing said first control signals and said first reference control signals; and
- operatively controlling said first apparatus in response to said first control signals when said first control signals and said first reference control signals equal each other;

characterised in that,

said method further comprises the following steps, which allows said first remote control device and said first apparatus to operatively control one or more second apparatus that are otherwise operatively responsive to respective second control signals from respective one or more second remote control devices:

- providing said first remote control device with additional operational functions, and corresponding third control signals, that respectively correspond to operational functions of said one or more second apparatus, said additional operational functions and third control signals being either selectively and/or permanently available;
- receiving and storing in said first apparatus, as part of an initialisation procedure and either in response to a request and/or as part of a predetermined sequence, said second control signals that have corresponding third control signals, said received second control signals being stored as second reference control signals in said storage medium;
- receiving said third control signals from said first remote control device;
- receiving second reference control signals from said storage



- 19 -

medium;

- comparing said third control signals and said second reference control signals; and  
- operatively controlling, by means of said second reference control signals, said one or more second apparatus, via said first apparatus, when said third control signals and said second reference control signals equal each other.

2. The method of claim 1, wherein said first apparatus remotely controls said one or more second apparatus.

3. A method according to claim 1 or claim 2, characterised in that said first apparatus is a set top box receiver.

4. A method according to any one of claims 1 to 3, characterised in that said one or more second apparatus include a video recorder and a television.

5. A method according to any one of claims 1 to 4, characterised in that said first apparatus is a video recorder.

6. A method according to any one of claims 1 to 5, characterised in that said one or more second apparatus include a set top box receiver and a television.

7. A method according to any one of claims 1 to 6, characterised in that said first apparatus is a television.

8. A method according to any one of claims 1 to 7, characterised in that said one or more second apparatus include a set top box receiver and a video recorder.

9. A method according to any of claims 1 to 8, characterised in that said one or more second apparatus include a sound system.

- 20 -

10. A method according to any of claims 1 to 9, characterised in that said one or more second apparatus include home automation apparatus.

11. A method according to any of claims 1 to 10, characterised in that said second control signals are received in response to a request from said first apparatus from said one or more second remote control devices.

12. A method according to any of claims 1 to 10, characterised in that said second control signals are received as part of a predetermined sequence from a portable storage medium.

13. A method according to claim 12, characterised in that said portable storage medium is a smartcard.

14. A method according to any of claims 1 to 10, characterised in that said second control signals are received as part of a predetermined sequence via said first apparatus's broadcast medium.

15. A method of controlling first and second remote controlled apparatus, the first apparatus being operatively responsive to first control signals associated with a first remote control device and the second apparatus being operatively responsive to second control signals associated with a second remote control device, the method comprising:

- storing said second control signals in said first apparatus;
- receiving the first control signals from the first remote control device at said first apparatus;
- accessing said stored second control signals responsive to selected ones of said first control signals; and
- transmitting said accessed second control signals to said second apparatus, wherein the first apparatus remotely controls the second apparatus responsive to selected ones of the first control signals from the first remote control device.

- 21 -

16. A remotely controlled apparatus, operatively responsive to first control signals, comprising:

- receiving means for receiving said first control signals from a first remote control device;
- storage means for storing second control signals associated with a second remotely controlled apparatus operatively responsive to said second control signals;
- control means for accessing said stored second control signals responsive to selected ones of said first control signals; and
- transmitting means for transmitting said accessed second control signals to said second remotely controlled apparatus, whereby the remotely controlled apparatus remotely controls the second remotely controlled apparatus.

17. The remotely controlled apparatus of claim 16, wherein said control means stores said second control signals in said storage means.

18. The remotely controlled apparatus of claim 16 or claim 17, further comprising:

- broadcast receiving means for receiving broadcast signals, wherein said second control signals are received by said broadcast receiving means.

19. The remotely controlled apparatus of claim 16 or claim 17, wherein said receiving means receives said second control signals from the second remote control device.

20. The remotely controlled apparatus of claim 14 wherein the storage means comprises a smart card.

21. A remote control system comprising:

- a first remotely controlled apparatus operationally responsive to first control signals associated with a first remote control device;
- a second remotely controlled apparatus operatively

- 22 -

responsive to second control signals associated with a second remote control device; wherein said first apparatus transmits said second control signals, to remotely control the second apparatus, responsive to selected ones of said first control signals.

22. The remote control system of claim 21 in which the first remotely controlled apparatus comprises the remotely controlled apparatus of any one of claims 16 to 20.

Figure 2





Figure 1



# INTERNATIONAL SEARCH REPORT

I. National Application No

PCT/GB 98/00956

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 6 H04B1/20

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H04B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 94 15 811 U (METZ WERKE GMBH & CO KG) 17 November 1994	1-9, 11, 14, 17, 19, 21, 22
A	see the whole document	10, 12, 13, 18, 20
X	US 5 081 534 A (GEIGER ERICH ET AL) 14 January 1992	1; 2, 4, 5, 7, 11, 15-17, 19, 21, 22
A	see line 13 - column 3, line 25; figures 1, 2	3, 6, 8-10, 12-14, 18, 20

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

° Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

29 July 1998

Date of mailing of the international search report

06/08/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Andersen, J.G.

# INTERNATIONAL SEARCH REPORT

I. national Application No

PCT/GB 98/00956

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 109 222 A (WELTY JOHN) 28 April 1992	1, 2, 4, 6, 8-11, 15-17, 19, 21, 22
A	see column 7, line 24 - column 8, line 19; figure 5	3, 5, 7, 12-14, 18, 20
A	EP 0 535 749 A (D2B SYSTEMS CO LTD) 7 April 1993 see page 2, line 25 - line 31	1, 12, 13, 15-17, 20



# INTERNATIONAL SEARCH REPORT

Information on patent family members

national Application No

PCT/GB 98/00956

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
DE 9415811	U	17-11-1994	DE 19534883 A	11-04-1996
US 5081534	A	14-01-1992	DE 3827050 A	15-02-1990
			AU 630367 B	29-10-1992
			AU 4037989 A	05-03-1990
			DE 58907163 D	14-04-1994
			DK 13591 A	25-01-1991
			WO 9001847 A	22-02-1990
			EP 0354459 A	14-02-1990
			EP 0433297 A	26-06-1991
			FI 100288 B	31-10-1997
			HK 7696 A	26-01-1996
			JP 4500142 T	09-01-1992
US 5109222	A	28-04-1992	NONE	
EP 0535749	A	07-04-1993	FI 924447 A	05-04-1993
			JP 5260058 A	08-10-1993
			US 5574965 A	12-11-1996